



Application

Seating
Walls require additional finishes.
Note: This leather can be used for aviation.

Characteristics

Content: 100% Leather
Finish: PFAS-Free Protective Topcoat
Backing: None
Dye Method: Transparent Dye and Pigment
Weight: 3 oz/sf (900 gr/sm)
Hide Size: 50-55 square feet (4.65-5.11 square meters)
Hide Thickness: 1.0-1.2 millimeters
Hide Origin: Europe
Country of Origin: Italy
Note: This material exhibits natural markings and inherent color and textural variations.

Price

Contact your sales representative for pricing.


Testing

Abrasion: ASTM D4157, 90,000 Double Rubs, Wzenbeek
ASTM D7255, 3 @ 1,000 Cycles

Flammability: BS 5852 Crib 5*
CAL 117-2013
*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours
Note: This material will lighten with prolonged exposure to heat or sunlight.

Maintenance

Professional cleaning recommended.


Environmental

Greenguard Gold Certified
LBC Red List Free
REACH Compliant
Produced In A Leather Working Group Silver Certified Facility
FR Free
Free of Intentionally Added PFAS

Warranty

None. See Terms and Conditions for more information.

© 2024 Edelman

Last updated August 2, 2025