Specifications All the Pandas 399625

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat Backing: None Reference Dimension: 11' H x 33' W (335cm x 1006cm) Traffic: Moderate Traffic Country of Origin: USA Note: Colors depicted are not an exact representation of the final product. Please request a substrate sample for accurate quality and color reference. Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment.

Price

Installation is sized, priced and produced on a project-specific basis.

Maintenance

W-Clean with water-based cleanser. ☆ ☆ ⊠ ⋧ ∞

Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours *** #**

Specifications All the Pandas 399625

Environmental Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Warranty

3 years.

Disclaimer

This artwork contains language or imagery that may not be suitable for all audiences.

© 2013 Rob Pruitt, Maharam under license

Complete product information at maharam.com 800.645.3943

