

# 300006 Amid

## maharam

#### Application

Walls

#### **Characteristics**

Content: 100% Non-Phthalate Vinyl Finish: PFAS-Free Protective Topcoat Backing: Polyester/Cotton Osnaburg Width: 52" (132cm) Repeat: 18" V, 52" H (46cm V, 132cm H) Bolt Size: 30 yards (27 m) Class: Type II Weight: 20 oz/ly (600 gr/lm) Traffic: High Traffic Country of Origin: USA Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

**Price** \$27.50 / C\$43.00 (FOB destination) C\$39.50 (FOB origin)

Testing Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered BS 476 Adhered\* CAN ULC S102 Adhered EN 13501 Adhered\* GB 8624 Adhered\* \*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours **\*** # **#** 

MaintenanceW/B-Clean with water-based cleanser or dilutedhousehold bleach. $\boxtimes \bigtriangleup \boxtimes \boxtimes$ 

**Environmental** FR Free Free of Intentionally Added PFAS Non-Phthalate Vinyl

#### Warranty

10 years. See Terms and Conditions for more information.

© 2018 Maharam

Last updated August 15, 2025

### maharam