



Application

Seating

Characteristics

Content: 100% Polyurethane/Silicone
Finish: PFAS-Free Ink-Resistant Protective Topcoat
Backing: Polyester
Width: 54" (137cm)
Bolt Size: 30 yards (27 m)
Weight: 22 oz/ly (700 gr/lm)
Country of Origin: Korea

Price

\$81.50 / C\$121.00 (FOB destination)
C\$116.50 (FOB origin)


Testing

Abrasion: ASTM D4157, 500,000 double rubs
Wyzenbeek
Note: Abrasion test results exceeding ACT
Performance Guidelines are not an indicator of
product lifespan. Multiple factors affect fabric
durability and appearance retention.

Flammability: AS/NZS 1530.3
AS/NZS 3837 Unadhered
BS 5852 Crib 5*
CAL 117-2013
EN 1021-1*
EN 1021-2*
GB/T 17591*
ISO 5660 Unadhered
NFPA 260
*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours


Maintenance

W/B-Clean with water-based cleanser or diluted
household bleach.


Environmental

Greenguard Gold Certified
Healthier Hospitals Compliant
LBC Red List Free
REACH Compliant
Produced in an ISO 14001 Facility
DMF Free
FR Free
Free of Intentionally Added PFAS

Warranty

5 years. See Terms and Conditions for more
information.

© 2017 Maharam

Last updated May 1, 2025