

Application

Walls

Characteristics

Content: 100% Cellulose

Finish: None

Backing: 84% Polyester, 16% Post-Consumer Recycled

Polyester

Width: 52" (132cm) Repeat: 72" V, 52" H (183cm V, 132cm H)

Bolt Size: 30 yards (27 m) Weight: 8.5 oz/ly (300 gr/lm)

Traffic: Moderate Traffic Country of Origin: USA

Note: This product is available in custom colors for a

minimum of 30 yards.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation

Guidelines included in each shipment.

Price

\$65.00 / C\$96.50 (FOB destination) C\$93.00 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered
CAN ULC S102 Adhered
EN 13501 Adhered*
ISO 5660 Adhered
*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Maintenance

W-Clean with water-based cleanser.



Environmental

Greenguard Gold Certified Healthier Hospitals Compliant

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Warranty

3 years. See Terms and Conditions for more information.

© 2019 Maharam

Last updated September 3, 2025