

Specifications

Bespoke Wall

300142

Knoll Textiles

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: PFAS-Free Protective Topcoat

Backing: Polyester/Cotton Osnaburg

Width: 50" (127cm)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: Great Britain

Note: Installation is sized and produced on a project-specific basis.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$10.75 / C\$20.01 (FOB destination) / C\$15.50 (FOB origin)

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Bespoke Wall
300142

Environmental
Free of Intentionally Added PFAS


Warranty
10 years.

© 2019 Knoll, Inc.

Complete product information at [knolltextiles.com](https://www.knolltextiles.com)
800.645.3943



001 Wilderness



002 Blushing



003 Crocus



004 Breeze



005 Malibu




006 Ficus




007 Goldfinch



008 Snapdragon



009 Mystic



010 Shade