

# Specifications

Knoll Textiles

Billow

300187

## Application

Walls

## Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: Protective Topcoat

Backing: Polyester/Cotton Osnaburg

Width: 52" (132cm)

Repeat: 22 1/4" V, 52" H

(57cm V, 132cm H)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

## Price

\$32.00 / C\$49.25 (FOB destination) / C\$45.75 (FOB origin)

## Maintenance

W-Clean with water-based cleanser.

## Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Specifications  
Billow  
300187

Knoll Textiles

Environmental  
Greenguard Certified

Warranty  
10 years.

© 2020 Knoll, Inc.

Complete product information at [knolltextiles.com](https://knolltextiles.com)  
800.645.3943



001 Ice Breaker



002 Sandstorm



003 Delta




004 Heatwave



005 Gust



006 Nimbus



007 Sumi



008 Spellbound



009 Thunder



010 Ink Wash