

Specifications

Knoll Textiles

Billow

300187

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 52" (132cm)

Repeat: 22 1/4" V, 52" H

(57cm V, 132cm H)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$32.00 / C\$50.25 (FOB destination) / C\$45.75 (FOB origin)

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Billow

300187

Environmental

Greenguard Certified

Free of Intentionally Added PFAS

Warranty

10 years.

© 2020 Knoll, Inc.

Complete product information at [knolltextiles.com](https://www.knolltextiles.com)

800.645.3943



001 Ice Breaker



002 Sandstorm



003 Delta



004 Heatwave



005 Gust



006 Nimbus



007 Sumi



008 Spellbound



009 Thunder



010 Ink Wash