

Specifications
Broken Stripe
by Alexander Girard, 1952
300091

Application

Walls

Characteristics

Content: 100% Cellulose

Finish: None

Backing: 84% Polyester, 16% Post-Consumer Recycled Polyester

Width: 52" (132cm)

Repeat: 18 1/4" V, 52" H

(46cm V, 132cm H)

Bolt Size: 30 yards (27 m)

Weight: 8.5 oz/ly (300 gr/lm)

Traffic: Moderate Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$72.50 / C\$107.25 (FOB destination) / C\$103.75 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

EN 13501 Adhered*

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Broken Stripe

by Alexander Girard, 1952

300091

maharam

Environmental

Greenguard Gold Certified
LBC Red List Free
REACH Compliant
Contains Bio-Based Content
FR Free
Free of Intentionally Added PFAS

Warranty

3 years.

© 2021 Girard Studio, LLC, Maharam under license

Complete product information at maharam.com
800.645.3943



001 Ochre and Blue
Gray Light



002 Emerald and
Turquoise Light



003 Gray Violet and
Viridian Light



004 Pink and Orange
Light



005 Crimson and
Orange



006 Peach and Raw
Umber



007 Crimson White
and Yellow Light



008 Violet and Navy



009 Madder Brown
and Sepia