

**Specifications**  
**Campagna Wall**  
**by Angelo Testa, 1947**  
**300252**

**Application**  
Walls

**Characteristics**

Content: 76% Thermoplastic Olefin, 24% Post-Industrial Recycled Thermoplastic Olefin

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 51" (130cm)

Repeat: 25" V, 51" H

(64cm V, 130cm H)

Bolt Size: 30 yards (27 m)

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

**Price**

\$38.00 / C\$58.00 (FOB destination) / C\$54.50 (FOB origin)

**Maintenance**

W-Clean with water-based cleanser.

**Testing**

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Specifications  
Campagna Wall  
by Angelo Testa, 1947  
300252

**Knoll Textiles**

**Environmental**

Greenguard Gold Certified  
Contains Recycled Content  
FR Free  
Free of Intentionally Added PFAS

**Warranty**

10 years.

© 2022 Knoll, Inc.

Complete product information at [knolltextiles.com](https://www.knolltextiles.com)  
800.645.3943



001 Gesso



002 Canvas




003 Linen



004 Fresco



005 Etching



006 Statue