

Specifications
Chambray
397140

maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl
Finish: None
Backing: Polyester/Cotton Osnaburg
Width: 54" (137cm)
Repeat: Non-match
Bolt Size: 30 yards (27 m)
Class: Type II
Weight: 20 oz/ly (600 gr/lm)
Traffic: High Traffic
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$26.50 / C\$41.50 (FOB destination) / C\$38.00 (FOB origin)

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Testing

Flammability: AS/NZS 3837 Adhered
ASTM E84 Adhered
BS 476 Adhered*
CAN ULC S102 Adhered
EN 13501 Adhered*
GB 8624 Adhered*
ISO 5660 Adhered
*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Specifications
Chambray
397140

maharam

Environmental

Greenguard Certified

FR Free

Free of Intentionally Added PFAS

Non-Phthalate Vinyl


Warranty

10 years.

© 2002 Maharam

Complete product information at maharam.com

800.645.3943



137 Shale