

Application

Walls

Characteristics

Content: 90% Thermoplastic Olefin, 10% Post-Industrial Recycled Glass
Finish: PFAS-Free Protective Topcoat
Backing: Polyester / Cellulose
Width: 52" (132cm)
Repeat: Non-match
Bolt Size: 30 yards (27 m)
Weight: 18 oz/ly (600 gr/lm)
Traffic: High Traffic
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$30.00 / C\$46.50 (FOB destination) / C\$43.00 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: ASTM E84 Adhered

Lightfastness: AATCC 16.3, + hours



Environmental

Greenguard Gold Certified
Contains Recycled Content
FR Free
Free of Intentionally Added PFAS

Warranty

10 years.

© 2025 Maharam

Complete product information at maharam.com
800.645.3943



001 Distant



002 Voile



003 Beech



004 Grain



005 Halcyon



006 Sundried



007 Cambium



008 Madder



009 Brandy



010 Pensive



011 Rye



012 Melancholy



013 Adagio



014 Mottled



015 Lucerne



016 Goodnight



017 Saratoga



018 Intuition



019 Saltwater



020 Whisper



021 Terrapin



022 Lemongrass