

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl
Finish: None
Backing: Cotton Osnaburg
Width: 52" (132cm)
Repeat: Non-match
Bolt Size: 27 yards (25 m)
Class: Type III
Weight: 35 oz/ly (1100 gr/lm)
Traffic: High Traffic
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$42.00 / C\$64.50 (FOB destination) / C\$60.00 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: ASTM E84 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Environmental

FR Free
Free of Intentionally Added PFAS

Warranty

10 years.

© 2017 Maharam

Complete product information at maharam.com
800.645.3943



001 Snowy



002 Mercury




003 Curry



004 Lemongrass




005 Mint



006 Juniper



007 Spray



008 Indigo




009 Periwinkle




010 Pixie




011 Mauve



012 Amethyst



013 Graphite



014 Coyote



015 Harvest




016 Sumatra



017 Mare



018 Hazel



019 Sandstone



020 Hot



021 Scarlet