

Specifications

Knoll Textiles

Contact

300198

Application

Walls

Characteristics

Content: 88% Non-Phthalate Vinyl, 12% Post-Industrial Recycled Non-Phthalate Vinyl

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 52" (132cm)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$28.00 / C\$43.50 (FOB destination) / C\$40.00 (FOB origin)

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

EN 13501 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Specifications
Contact
300198

Environmental
Greenguard Certified
Contains Recycled Content
FR Free
Free of Intentionally Added PFAS

Warranty
10 years.

© 2023 Knoll, Inc.

Complete product information at knolltextiles.com
800.645.3943



001 Diamond



002 Etch



003 Bark



004 Timber




005 Husk



006 Leaf



007 Dragonfly




008 Stream



009 Bridge



010 Chain



011 Ore