

300156 Counter Point Knoll Textiles

Application

Upholstered Walls, Walls

Characteristics

Content: 43% Solution-Dyed Polyolefin, 31% Solution-Dyed Polyester, 26% Solution-Dyed Polyethylene

Finish: PFAS-Free Water Repellent

Backing: Acrylic Width: 54" (137cm) Repeat: 10" V, 14 1/4" H (25cm V, 36cm H)

Bolt Size: 55 yards (50 m) Weight: 10 oz/ly (300 gr/lm)

Traffic: High Traffic
Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at

maharam.com.

Price

\$42.50 / C\$64.25 (FOB destination) C\$60.75 (FOB origin)

Testing

Acoustics: ASTM C423, 0.95 NRC

Flammability: ASTM E84 Adhered*

ASTM E84 Unadhered* CAN ULC S102 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Environmental

Greenguard Gold Certified

LBC Red List Free

Free of Intentionally Added PFAS

Warranty

10 years. See Terms and Conditions for more information.

© 2019 Knoll, Inc.

Last updated August 2, 2025