

Specifications

Cue

399634

maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: PFAS-Free Protective Topcoat

Backing: Polyester/Cotton Osnaburg

Width: 54" (137cm)

Repeat: Non-match

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$30.00 / C\$46.50 (FOB destination) / C\$43.00 (FOB origin)

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

☒ △ ☒ ☒ Ⓜ

Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

BS 476 Adhered*

CAN ULC S102 Adhered

EN 13501 Adhered*

GB 8624 Adhered*

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours

☀ 🔥 🖨

Specifications
Cue
399634

maharam

Environmental

FR Free
Free of Intentionally Added PFAS
Non-Phthalate Vinyl

Warranty

10 years.

© 2014 Maharam

Complete product information at maharam.com
800.645.3943



003 Doe



004 Beige



005 Mill



006 Cloud



007 Shoal



008 Dorado



013 Porpoise



014 Atmosphere



016 Arctic



017 Placid