

Specifications

Knoll Textiles

Debut
300188

Application Walls

Characteristics

Content: 100% Non-Phthalate Vinyl
Finish: PFAS-Free Protective Topcoat
Backing: 52% Pc Recycled Cellulose, 28% Cellulose, 20% Polyester
Width: 54" (137cm)
Repeat: 25 1/4" V, 25 1/4" H
(64cm V, 64cm H)
Bolt Size: 30 yards (27 m)
Class: Type II
Weight: 20 oz/ly (600 gr/lm)
Traffic: High Traffic
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$28.00 / C\$43.50 (FOB destination) / C\$40.00 (FOB origin)

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: ASTM E84 Adhered
CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Debut
300188

Environmental
Greenguard Certified
Free of Intentionally Added PFAS

Warranty
10 years.

© 2020 Knoll, Inc.


Complete product information at [knolltextiles.com](https://www.knolltextiles.com)
800.645.3943



001 Poised




002 Solo



003 Laurel



004 Crown




005 Bravo



006 Headline



007 Concert



008 Pedestal



009 Fame



010 City Lights