Specifications Digital Ikat 300165

Application Upholstered Walls, Walls

Characteristics

Content: 90% Polyester, 10% Thermoplastic Olefin Finish: None Backing: Acrylic Width: 51" (130cm) Repeat: 60" V, 51" H (152cm V, 130cm H) Bolt Size: 50 yards (46 m) Weight: 20 oz/ly (600 gr/lm) Traffic: High Traffic Country of Origin: Korea Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$63.00 / C\$93.50 (FOB destination) / C\$90.00 (FOB origin)

Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Testing

Flammability: ASTM E84 Adhered ASTM E84 Unadhered CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours

* # • *

Specifications Digital Ikat 300165


Environmental Greenguard Gold Certified LBC Red List Free Free of Intentionally Added PFAS

Warranty 10 years.

© 2022 Knoll, Inc.

Complete product information at knolltextiles.com 800.645.3943









001 Unwind

003 Vista

004 Harmonic

005 Magnet