

# Specifications

Knoll Textiles

Drift

300144

## Application

Walls

## Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: PFAS-Free Protective Topcoat

Backing: 52% Pc Recycled Cellulose, 28% Cellulose, 20% Polyester

Width: 54" (137cm)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note: Slight variations in pattern are inherent to this textile.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

## Price

\$29.00 / C\$45.00 (FOB destination) / C\$41.50 (FOB origin)

## Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

☒ △ ☒ ☒ Ⓜ

## Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours

☼ 🔥 🖨️ ☆

Specifications

Drift

300144

Environmental

Greenguard Certified

Free of Intentionally Added PFAS

Warranty

10 years.

© 2020 Knoll, Inc.

Complete product information at [knolltextiles.com](https://www.knolltextiles.com)

800.645.3943




001 Windswept




002 Sound Wave




003 Waterway



004 Palm



005 Basin



006 Storm



007 Flurry



008 Scale



009 Marine