Specifications Elixir 300179

Application Walls

Characteristics

Content: 86% Thermoplastic Olefin, 14% Post-Industrial Recycled Glass Finish: PFAS-Free Protective Topcoat Backing: Polyester / Cellulose Width: 50" (127cm) Repeat: 60" V, 50" H (152cm V, 127cm H) Bolt Size: 35 yards (32 m) Weight: 18 oz/ly (600 gr/lm) Traffic: High Traffic Country of Origin: USA Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price \$58.50 / C\$87.25 (FOB destination) / C\$83.75 (FOB origin)

Maintenance W-Clean with water-based cleanser. ☆ ☆ ⊠ ☆ ∞

Testing Flammability: ASTM E84 Adhered CAN ULC S102 Adhered


Specifications Elixir 300179

Environmental Greenguard Gold Certified Healthier Hospitals Compliant **Contains Recycled Content** FR Free Free of Intentionally Added PFAS Made In USA

Warranty 10 years.

© 2024 Knoll, Inc.

Complete product information at knolltextiles.com 800.645.3943



001 Robust

003 Scramble

004 Perch

006 Jungle