

Specifications

Filter

300069

maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: PFAS-Free Protective Topcoat

Backing: Cotton Osnaburg

Width: 54" (137cm)

Repeat: Non-match

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$30.00 / C\$46.50 (FOB destination) / C\$43.00 (FOB origin)

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

BS 476 Adhered

CAN ULC S102 Adhered

EN 13501 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, + hours



Environmental

Greenguard Certified
FR Free
Free of Intentionally Added PFAS
Non-Phthalate Vinyl

Warranty

10 years.

© 2020 Maharam

Complete product information at maharam.com
800.645.3943



001 Silkworm



002 Icebox



003 Stonework



004 Sandpiper



005 Flower



006 Orrery



007 Candlelit



008 Pufferfish




009 Abalone



010 Outside



011 Idyllic




012 Windsurf



013 Skyscape



014 Seasoning



015 Serene



016 Moonrise