

# Specifications

## Fine Print

300216

**Knoll Textiles**

### Application

Walls

### Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: Protective Topcoat

Backing: Polyester/Cotton Osnaburg

Width: 54" (137cm)

Repeat: 22 1/4" V

(57cm V)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

### Price

\$38.50 / C\$58.50 (FOB destination) / C\$55.00 (FOB origin)

### Maintenance

W-Clean with water-based cleanser.

### Testing

Flammability: ASTM E84 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications  
Fine Print  
300216

**Environmental**  
Greenguard Certified  
Non-Phthalate Vinyl

**Warranty**  
10 years.

© 2004 Knoll, Inc.

Complete product information at [knolltextiles.com](http://knolltextiles.com)  
800.645.3943




002 Silkscreen



003 Wax Transfer




016 Cornsilk



017 Type Block



020 Plaster Board



028 Electro Plate