

# Specifications

Flaxen

397130

**maharam**

## Application

Walls

## Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 54" (137cm)

Repeat: Non-match

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

## Price

\$26.50 / C\$41.50 (FOB destination) / C\$38.00 (FOB origin)

## Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

☒ △ ☒ ☒ Ⓜ

## Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

BS 476 Adhered\*

CAN ULC S102 Adhered

EN 13501 Adhered\*

GB 8624 Adhered\*

ISO 5660 Adhered

\*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours

☀ 🔥 🖨

Specifications  
Flaxen  
397130

**maharam**

**Environmental**

Greenguard Certified

FR Free

Free of Intentionally Added PFAS

Non-Phthalate Vinyl


**Warranty**

10 years.

© 2002 Maharam

Complete product information at [maharam.com](http://maharam.com)

800.645.3943



125 Dove