



125 Dove

397130 Flaxen

maharam

Application Walls	Price \$26.50 / C\$41.50 (FOB destination) C\$38.00 (FOB origin)	Maintenance W/B-Clean with water-based cleanser or diluted household bleach. ☒ △ ☒ ☒ Ⓜ
Characteristics Content: 100% Non-Phthalate Vinyl Finish: None Backing: Polyester/Cotton Osnaburg Width: 54" (137cm) Repeat: Non-match Bolt Size: 30 yards (27 m) Class: Type II Weight: 20 oz/ly (600 gr/lm) Traffic: High Traffic Country of Origin: USA Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.	Testing Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered BS 476 Adhered* CAN ULC S102 Adhered EN 13501 Adhered* GB 8624 Adhered* ISO 5660 Adhered *passes with additional treatment Lightfastness: AATCC 16.3, 200+ hours ☀️ 🔥 🖨️	Environmental Greenguard Certified FR Free Free of Intentionally Added PFAS Non-Phthalate Vinyl Warranty 10 years. See Terms and Conditions for more information. © 2002 Maharam Last updated August 2, 2025