

Application

Walls

Characteristics

Content: 90% Thermoplastic Olefin, 10% Post-Industrial Recycled Glass

Finish: None

Backing: Polyester / Cellulose

Width: 52" (132cm)

Repeat: 18" V, 51 1/2" H

(46cm V, 131cm H)

Bolt Size: 30 yards (27 m)

Weight: 18 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$31.00 / C\$49.00 (FOB destination) / C\$44.50 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Environmental

Greenguard Gold Certified
Healthier Hospitals Compliant
LBC Red List Free
Contains Recycled Content
FR Free
Free of Intentionally Added PFAS

Warranty

10 years.

© 2024 Maharam


Complete product information at maharam.com
800.645.3943



001 Rule



002 Inclement



003 Shaker



004 Habanero



005 Peanut



006 Goldfinch



007 Fern



008 Voyage



009 Cascade



010 Diver



011 Heron



012 Flight



013 Altitude



014 Dice