

Design

Alexander Girard, 1961

Collection

Textiles of the 20th Century

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester / Cellulose

Width: 52" (132cm) Repeat: 24" V, 13" H (61cm V, 33cm H)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at

maharam.com.

Price

\$44.50 / C\$67.25 (FOB destination) C\$63.75 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered
CAN ULC S102 Adhered
EN 13501 Adhered*
GB 8624 Adhered*
ISO 5660 Adhered
*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Environmental

FR Free

Free of Intentionally Added PFAS

Non-Phthalate Vinyl

Warranty

10 years. See Terms and Conditions for more information.

© 2015 Girard Studio, LLC, Maharam under license

Last updated June 16, 2025