

Specifications

Graze

300009

maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: PFAS-Free Protective Topcoat (Impermeable)

Backing: Polyester/Cotton Osnaburg

Width: 54" (137cm)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$25.25 / C\$39.75 (FOB destination) / C\$36.25 (FOB origin)

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

BS 476 Adhered*

CAN ULC S102 Adhered

EN 13501 Adhered*

GB 8624 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Specifications

Graze

300009

maharam

Environmental

Greenguard Certified
FR Free
Free of Intentionally Added PFAS
Non-Phthalate Vinyl

Warranty

10 years.

© 2018 Maharam

Complete product information at maharam.com
800.645.3943




001 Floe



002 Sardine



003 Allure



004 Marcasite



005 Herald



006 Rosy




007 Figure



008 Cake



009 Limestone



010 Stamen




011 Millet




012 Nacre



013 View



014 Underwater



015 Astral