

300009 Graze maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None (Impermeable)

Backing: Polyester/Cotton Osnaburg

Width: 54" (137cm)

Bolt Size: 30 yards (27 m)

Class: Type II

maharam.com.

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation

Guidelines included in each shipment or available at

Price

\$24.50 / C\$38.25 (FOB destination) C\$34.75 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered BS 476 Adhered*

CAN ULC S102 Adhered EN 13501 Adhered*

GB 8624 Adhered*
*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours

* # G

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

 $\boxtimes \triangle \boxtimes \boxtimes \otimes$

Environmental

Greenguard Certified

FR Free

Free of Intentionally Added PFAS

Non-Phthalate Vinyl

Warranty

10 years. See Terms and Conditions for more information.

© 2018 Maharam

Last updated May 1, 2025