

# Specifications

## Headline

300199

### Application

Walls

### Characteristics

Content: 63% Thermoplastic Olefin, 37% Post-Industrial Recycled Thermoplastic Olefin

Finish: PFAS-Free Protective Topcoat

Backing: None

Width: 52" (132cm)

Bolt Size: 25 yards (23 m)

Weight: 33 oz/ly (1000 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

### Price

\$50.50 / C\$75.75 (FOB destination) / C\$72.25 (FOB origin)

### Maintenance

W-Clean with water-based cleanser.

### Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Specifications

Headline

300199

Knoll Textiles

**Environmental**  
Greenguard Gold Certified  
Contains Recycled Content  
FR Free  
Free of Intentionally Added PFAS


**Warranty**  
10 years.

© 2023 Knoll, Inc.

Complete product information at [knolltextiles.com](https://knolltextiles.com)  
800.645.3943




001 Lace



002 Echo




003 Sunglow



004 Oxygen




005 Russet



006 Biscuit



007 Gunmetal



008 Admiral