

Specifications

Knoll Textiles

Headline

300199

Application

Walls

Characteristics

Content: 63% Thermoplastic Olefin, 37% Post-Industrial Recycled Thermoplastic Olefin

Finish: None

Backing: None

Width: 52" (132cm)

Bolt Size: 25 yards (23 m)

Weight: 33 oz/ly (1000 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$50.50 / C\$76.75 (FOB destination) / C\$72.25 (FOB origin)

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Specifications

Headline

300199

Knoll Textiles

Environmental
Greenguard Gold Certified
Contains Recycled Content
FR Free
Free of Intentionally Added PFAS


Warranty
10 years.

© 2023 Knoll, Inc.

Complete product information at knolltextiles.com
800.645.3943




001 Lace



002 Echo




003 Sunglow



004 Oxygen




005 Russet



006 Biscuit



007 Gunmetal



008 Admiral