

## Specifications

Ikebana

399485

**maharam**

### Application

Walls

### Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 16' 8" W (305cm x 508cm)

Traffic: Moderate Traffic

Customs: Scalable

Country of Origin: USA

Note: Colors depicted are not an exact representation of the final product. Please request a substrate sample for accurate quality and color reference.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](https://maharam.com).

### Price

Installation is sized, priced and produced on a project-specific basis.

### Maintenance

W-Clean with water-based cleanser.



### Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



## Specifications

Ikebana

399485

**maharam**

### **Environmental**

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

### **Warranty**

3 years.

© 2010 Jon Kessler, Maharam under license

Complete product information at [maharam.com](http://maharam.com)

800.645.3943



001