







001

Design

Udomsak Krisanamis

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 16' 8" W (305cm x 508cm)

Traffic: Moderate Traffic

Customs: Repeatable, Scalable

Country of Origin: USA

Note: Colors depicted are not an exact representation of the final product. Please request a substrate sample for accurate quality and color reference.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis.

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Environmental

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Brief

For Infinity, Udomsak Krisanamis used a graphic palette of found calendar pages. The number eight, which is considered lucky by many Asian cultures, is a recurring motif for Krisanamis. Here, it represents the concept of infinity, which in turn relates to the potential of the pattern to repeat forever and the limitless nature of time.

Warranty

3 years. See Terms and Conditions for more information.

© 2012 Udomsak Krisanamis, Maharam under license

Last updated August 18, 2025