

# Specifications

Knoll Textiles

Ion

300170

## Application

Walls

## Characteristics

Content: 87% Solution-Dyed Polyolefin, 13% Post-Consumer Recycled Polyester

Finish: None

Backing: Acrylic

Width: 55" (140cm)

Bolt Size: 40 yards (37 m)

Weight: 13.5 oz/ly (400 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

## Price

\$30.50 / C\$47.25 (FOB destination) / C\$43.75 (FOB origin)

## Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

## Testing

Acoustics: ASTM C423, 0.75 NRC

Flammability: ASTM E84 Adhered

ASTM E84 Unadhered

CAN ULC S102 Adhered

CAN ULC S102 Unadhered

EN 13501 Adhered\*

\*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Ion

300170

Knoll Textiles

**Environmental**  
Greenguard Gold Certified  
LBC Red List Free  
Contains Recycled Content  
FR Free  
Free of Intentionally Added PFAS

**Warranty**  
10 years.

© 2024 Knoll, Inc.

Complete product information at [knolltextiles.com](https://knolltextiles.com)  
800.645.3943




001 Easy




002 Field



003 Spruce



004 Lagoon



005 Sumac



006 Outward



007 Stormy



008 Royal