

# Specifications

**maharam**

Ito  
399970

## Application

Walls

## Characteristics

Content: 65% Cellulose, 35% Latex  
Finish: PFAS-Free Protective Topcoat  
Backing: None  
Reference Dimension: 10' H x 36' 8" W (305cm x 1118cm)  
Traffic: Moderate Traffic  
Customs: Repeatable, Scalable  
Country of Origin: USA  
Note: Colors depicted are not an exact representation of the final product. Please request a substrate sample for accurate quality and color reference.  
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.  
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

## Price

Installation is sized, priced and produced on a project-specific basis.

## Maintenance

W-Clean with water-based cleanser.



## Testing

Flammability: AS/NZS 3837 Adhered  
ASTM E84 Adhered  
CAN ULC S102 Adhered  
ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



## Specifications

Ito

399970

**maharam**

### **Environmental**

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

### **Warranty**

3 years.

© 2017 Miranda Lichtenstein, Maharam under license

Complete product information at [maharam.com](https://maharam.com)

800.645.3943



001