

Specifications

Line Work

300193

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: PFAS-Free Protective Topcoat

Backing: Polyester/Cotton Osnaburg

Width: 53" (135cm)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$30.50 / C\$47.25 (FOB destination) / C\$43.75 (FOB origin)

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

☒ △ ☒ ☒ ☒ Ⓜ

Testing

Flammability: ASTM E84 Adhered

Lightfastness: AATCC 16.3, 40+ hours

☼ 🔥 🖤 ☆

Specifications
Line Work
300193

Environmental
Greenguard Certified
Free of Intentionally Added PFAS

Warranty
10 years.

© 2018 Knoll, Inc.

Complete product information at knolltextiles.com
800.645.3943




001 Parchment



002 Rosewater




003 Rodeo




004 Waterfall



005 Burnished



006 Hummingbird



007 Dapper