



399670 Lines

maharam



001

Design

Scholten & Baijings

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 36' 8" W (305cm x 1118cm)

Traffic: Moderate Traffic

Customs: Repeatable

Country of Origin: USA

Note: Colors depicted are not an exact representation of the final product. Please request a substrate sample for accurate quality and color reference.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis.

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Environmental

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Brief

Lines' shifting light and dark fields are achieved through varying densities of parallel and perpendicular lines. Grayscale offers a subtle rendering in a departure from Scholten & Baijings' typical color palette.

Warranty

3 years. See Terms and Conditions for more information.

© 2015 Scholten & Baijings, Maharam under license

Last updated August 2, 2025