001 Siberia	002 Cream

399632 Lucid

maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl Finish: PFAS-Free Protective Topcoat Backing: Polyester/Cotton Osnaburg Width: 54" (137cm) Repeat: Non-match Bolt Size: 30 yards (27 m) Class: Type II Weight: 20 oz/ly (600 gr/lm) Traffic: High Traffic Country of Origin: USA Note on Mold: Intended for use in build

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com. **Price** \$30.00 / C\$46.50 (FOB destination) C\$43.00 (FOB origin)

Testing Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered BS 476 Adhered* CAN ULC S102 Adhered EN 13501 Adhered* GB 8624 Adhered* ISO 5660 Adhered *passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours

MaintenanceW/B-Clean with water-based cleanser or dilutedhousehold bleach. $\Join \land \boxtimes ~ \Join ~ \oslash$

Environmental FR Free Free of Intentionally Added PFAS Non-Phthalate Vinyl

Warranty

10 years. See Terms and Conditions for more information.

© 2014 Maharam

Last updated August 21, 2025

399632 Lucid

maharam