

Specifications  
Merge  
by Abbott Miller  
300205

Knoll Textiles

Application  
Walls

Characteristics

Content: 100% Non-Phthalate Vinyl  
Finish: Protective Topcoat  
Backing: Polyester/Cotton Osnaburg  
Width: 54" (137cm)  
Repeat: 22 1/4" V  
(57cm V)  
Bolt Size: 30 yards (27 m)  
Class: Type II  
Weight: 20 oz/ly (600 gr/lm)  
Traffic: High Traffic  
Country of Origin: USA  
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.  
Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

Price

\$45.00 / C\$68.00 (FOB destination) / C\$64.50 (FOB origin)

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: ASTM E84 Adhered

Lightfastness: AATCC 16.3, 40+ hours



**Specifications**

**Merge**

by Abbott Miller

300205

**Environmental**

Greenguard Certified


**Warranty**

10 years.

© 2006 Knoll, Inc.

Complete product information at [knolltextiles.com](http://knolltextiles.com)

800.645.3943



002 Cloud Gray



004 French Gray



007 Mars Black



008 Cadmium