Specifications Nook 399913

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl Finish: PFAS-Free Protective Topcoat Backing: Polyester/Cotton Osnaburg Width: 54" (137cm) Repeat: Non-match Bolt Size: 30 yards (27 m) Class: Type II Weight: 20 oz/ly (600 gr/lm) Traffic: High Traffic Country of Origin: USA Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$41.50 / C\$63.00 (FOB destination) / C\$59.50 (FOB origin)

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach. $\boxtimes \ \bigtriangleup \ \boxtimes \ \boxtimes$

Testing

Flammability: ASTM E84 Adhered BS 476 Adhered* CAN ULC S102 Adhered EN 13501 Adhered* GB 8624 Adhered* *passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours # # #

Specifications Nook 399913

Environmental

FR Free Free of Intentionally Added PFAS Non-Phthalate Vinyl

Warranty

10 years.

© 2016 Maharam

Complete product information at maharam.com 800.645.3943



022 Cormorant

023 Starlight (

024 Cave