Specifications Ore 300058

Application

Walls

Characteristics

Content: 70% Cellulose, 30% Polyester Finish: PFAS-Free Water Repellent Backing: Cellulose / Polyester Width: 54" (137cm) Repeat: 16 3/4" H (43cm H) Bolt Size: 55 yards (50 m) Weight: 15.2 oz/ly (500 gr/lm) Traffic: Moderate Traffic Country of Origin: Netherlands Note: Variations in color and texture are inherent to this textile. Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$81.50 /

Maintenance

X-Vacuum or brush lightly to remove surface dust. ☆ ☆ ⊠ ≳ ∞

Testing Flammability: ASTM E84 Adhered EN 13501 Adhered

Lightfastness: AATCC 16.3, 40+ hours

Specifications Ore 300058

Environmental

Greenguard Gold Certified Healthier Hospitals Compliant LBC Red List Free **REACH** Compliant Contains Bio-Based Content Contains Forest Stewardship Council (Fsc) Certified Content FR Free Free of Intentionally Added PFAS

Warranty

1 year.

© 2019 Maharam

Complete product information at maharam.com 800.645.3943

