

**Specifications**  
**Overlay**  
**by Kari Pei**  
**300221**

**Application**  
Walls

**Characteristics**

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 53" (135cm)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

**Price**

\$42.50 / C\$65.25 (FOB destination) / C\$60.75 (FOB origin)

**Maintenance**

W-Clean with water-based cleanser.

**Testing**

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications  
Overlay  
by Kari Pei  
300221

**Environmental**  
Free of Intentionally Added PFAS

**Warranty**  
10 years.

© 2014 Knoll, Inc.


Complete product information at [knolltextiles.com](http://knolltextiles.com)  
800.645.3943



001 Alabaster



002 Enamel



005 Fire Glaze



007 Silver