



001 Talc



002 Zinc



003 Tusk



004 Aloe



005 Magnetism



006 Dry Plain



007 Bleached Pine

Design

Suzanne Tick

Application

Upholstered Walls, Walls

Characteristics

Content: 58% Polyolefin, 42% Polyester

Finish: PFAS-Free Water Repellent

Backing: Acrylic

Width: 54" (137cm)

Bolt Size: 55 yards (50 m)

Weight: 16 oz/ly (500 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation

Guidelines included in each shipment or available at maharam.com.

Price

\$54.50 / C\$81.50 (FOB destination)

C\$78.00 (FOB origin)

Testing

Acoustics: ASTM C423, 1.00 NRC

Flammability: ASTM E84 Adhered

ASTM E84 Unadhered

EN 13501 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Environmental

Greenguard Gold Certified

LBC Red List Free

FR Free

Free of Intentionally Added PFAS

Warranty

10 years. See Terms and Conditions for more information.

© 2010 Knoll, Inc.

Last updated August 1, 2025