Of Florete

Ultimate

202 International and a second sec

Of Cachined

005 Musli

009 Graphite

[11:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
[20:10]
<t

010 Electrum

901898 Photon II

007 Alur

Knoll Textiles

Design Suzanne Tick

Application Seating, Systems, Upholstered Walls, Windows

Characteristics

Content: 50% Polyester, 50% Post-Industrial Recycled Polyester Finish: None Backing: None Width: 66" (168cm) Repeat: 11/4" V, 1/2" H (3cm V, 1cm H) Bolt Size: 75 yards (69 m) Weight: 11.3 oz/ly (300 gr/lm) Country of Origin: USA Price \$50.50 / C\$75.75 (FOB destination) C\$72.25 (FOB origin)

Testing

Abrasion: ASTM D4157, 40,000 double rubs Wyzenbeek Note: Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Acoustics: ASTM C423, 0.95 NRC

Flammability: ASTM E84 Unadhered CAL 117-2013 CAN ULC S102 Unadhered NFPA 260 NFPA 701

Lightfastness: AATCC 16.3, 60+ hours

Maintenance W/S/B-Clean with water-based cleanser; mild, waterfree dry cleaning solvent, or diluted household bleach.

Environmental

Greenguard Gold Certified LBC Red List Free Contains Recycled Content FR Free Free of Intentionally Added PFAS

Warranty

3 years. See Terms and Conditions for more information.

© 2012 Knoll, Inc.

Last updated August 2, 2025