



Design

Scholten & Baijings

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 53' W (305cm x 1615cm)

Traffic: Moderate Traffic

Customs: Repeatable, Scalable

Country of Origin: USA

Note: Colors depicted are not an exact

representation of the final product. Please request a substrate sample for accurate quality and color

reference.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis.

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Environmental

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free

Free of Intentionally Added PFAS

Brief

In Planes, Scholten & Baijings explore color blocking through neutral tints accented by highlighter yellows. With a balanced yet dynamic composition, color fields shift from foreground to background.

Warranty

3 years. See Terms and Conditions for more information.

© 2015 Scholten & Baijings, Maharam under license

Last updated August 18, 2025