

Specifications

Premier

466920

Application

Seating

Characteristics

Content: 100% Silicone

Finish: None

Backing: Polyester

Width: 54" (137cm)

Bolt Size: 30 yards (27 m)

Weight: 28 oz/ly (900 gr/lm)

Country of Origin: Korea

Price

\$73.50 / C\$108.50 (FOB destination) / C\$105.00 (FOB origin)

Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Testing

Abrasion: ASTM D4157, 200,000 double rubs Wyzenbeek

Note: Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

Multiple factors affect fabric durability and appearance retention.

Flammability: ASTM E84 Adhered

BS 5852 Crib 5

CAL 117-2013

FMVSS 302

Lightfastness: AATCC 16.3, + hours

ASTM G154, + hours



Specifications

Premier

466920

Knoll Textiles

Environmental

Greenguard Gold Certified

LBC Red List Free

FR Free

Free of Intentionally Added PFAS

Warranty

5 years.

© 2019 Knoll, Inc.

Complete product information at [knolltextiles.com](https://www.knolltextiles.com)

800.645.3943

Specifications
Premier
466920

Knoll Textiles

