

Application

Walls

Characteristics

Content: 70% Cellulose, 30% Polyester

Finish: PFAS-Free Water Repellent

Backing: Cellulose / Polyester

Width: 54" (137cm)

Repeat: 1/4" H

(1cm H)

Bolt Size: 55 yards (50 m)

Weight: 8.4 oz/ly (300 gr/lm)

Traffic: Moderate Traffic

Country of Origin: Netherlands

Note: Variations in color and texture are inherent to this textile.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$43.50 /

Maintenance

X-Vacuum or brush lightly to remove surface dust.



Testing

Flammability: ASTM E84 Adhered

EN 13501 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Environmental

Greenguard Gold Certified
Healthier Hospitals Compliant
LBC Red List Free
REACH Compliant
Contains Bio-Based Content
Contains Forest Stewardship Council (Fsc) Certified Content
FR Free
Free of Intentionally Added PFAS

Warranty

1 year.

© 2019 Maharam

Complete product information at maharam.com
800.645.3943



001 Verglas



002 Swank



003 Excelsior



004 Magnate



005 Myna



006 Accordion



007 Atelier



008 Foretell



009 University