

399977 Relic maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 54" (137cm)

Bolt Size: 30 yards (27 m)

Class: Type II

maharam.com.

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note: This product uses iridescent inks which produce subtle variations in color when viewed from different

angles and under different light sources.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at

Price

\$31.50 / C\$49.50 (FOB destination) C\$45.00 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered BS 476 Adhered*

CAN ULC S102 Adhered EN 13501 Adhered* GB 8624 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Environmental

FR Free

Free of Intentionally Added PFAS

Non-Phthalate Vinyl

Warranty

10 years. See Terms and Conditions for more information.

© 2018 Maharam

Last updated May 1, 2025