

Specifications

Renard 2

399445

maharam

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 16' 8" W (305cm x 508cm)

Traffic: Moderate Traffic

Customs: Scalable

Country of Origin: USA

Note: Colors depicted are not an exact representation of the final product. Please request a substrate sample for accurate quality and color reference.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis.

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Renard 2

399445

maharam

Environmental

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Warranty

3 years.

Disclaimer

This artwork contains language or imagery that may not be suitable for all audiences.

© 2009 Harmen Liemburg, Maharam under license

Complete product information at maharam.com

800.645.3943



001