

Specifications
Roman Stripe
by Alexander Girard, 1952
300093

Application

Walls

Characteristics

Content: 100% Cellulose

Finish: None

Backing: 84% Polyester, 16% Post-Consumer Recycled Polyester

Width: 52" (132cm)

Repeat: Non-match

Bolt Size: 30 yards (27 m)

Weight: 8.5 oz/ly (300 gr/lm)

Traffic: Moderate Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$72.50 / C\$108.25 (FOB destination) / C\$103.75 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

EN 13501 Adhered*

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Roman Stripe
by Alexander Girard, 1952
300093

maharam

Environmental

Greenguard Gold Certified
LBC Red List Free
REACH Compliant
Contains Bio-Based Content
FR Free
Free of Intentionally Added PFAS

Warranty

3 years.

© 2021 Girard Studio, LLC, Maharam under license

Complete product information at maharam.com
800.645.3943



001 Raw Umber On
Dark Gray



002 White On Light
Gray




003 Ochre On White



004 Gray On Light
Ochre



005 Orange On Dark
Gray



006 Crimson On
Light Gray



007 Ultramarine
White On Raw
Umber