

Design

Alexander Girard, 1952

Collection

Textiles of the 20th Century

Application

Walls

Characteristics

Content: 100% Cellulose

Finish: None

Backing: 84% Polyester, 16% Post-Consumer Recycled

Polyester

Width: 52" (132cm) Repeat: Non-match Bolt Size: 30 yards (27 m)

Weight: 8.5 oz/ly (300 gr/lm)

Traffic: Moderate Traffic Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation

Guidelines included in each shipment or available at

maharam.com.

Price

\$72.50 / C\$107.25 (FOB destination) C\$103.75 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered CAN ULC S102 Adhered EN 13501 Adhered* ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Maintenance

W-Clean with water-based cleanser.

Environmental

Greenguard Gold Certified

LBC Red List Free REACH Compliant

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Warranty

3 years. See Terms and Conditions for more information.

© 2021 Girard Studio, LLC, Maharam under license

Last updated August 15, 2025